# YHC series hidden type of air shower nozzles







YHC-ABS
Plastic chrome plating



YHC-LD Large diameter

#### **DESIGN FEATURES**

The air shower nozzle is ideal accessory for air shower room and cleaning room adopting the unique uneven direction nozzle, can easily assures the air jet direction and maintain the ideal air current structure in shower room.

YHC air shower nozzle reduces the blowing noise to a great extent, It consists of a back cover (with a gasket), an adjustable globe, bellmouth and a hidden frame.

The airflow rate of 20m/s at outlet can blow off the dust efficiently with a good cost effectiveness. The available material can be stainless steel, single side electroplate board, electrolysis board, engineering plastics etc.

Other material may be adopted for special applications.






### **DIMENSIONS**

		Dimension(mm)						
Туре	Ball dia.(mm)	h1	h2	h3	h4	D1		
	00/00/00	165.5	61.6	145	12	3		
3666HYC-SS	20/30/38	165.5	61.6	150	18	3		
3666HYC-ABS	20/30/38	176	71	156	18	3		
3666HYC-SS(large)	45/70/75	217	75	188	18	3		





### PARAMETER OF YHC

Туре	Material code		Effective	Air blowing spit volume						
	SS	ABS	Large dia. SS	area(m²)	Section and	V=3m/s	V=4m/s	V=5m/s	V=6m/s	V=7m/s
YHC20	•	•		3.14*10 <sup>-4</sup>	2.3	3.4	4.5	5.7	6.8	7.9
YHC30	•	•		0.7*10 <sup>-3</sup>	5	7	10	12	15	17
THC38	•	•		1.13*10 <sup>-3</sup>	8	12	16	20	24	28
YHC40			•	1.26*10 <sup>-3</sup>	9	14	18	23	27	32
YHC70			•	3.84*10 <sup>-3</sup>	28	40	55	69	83	97





## **COMMON APPLICATIONS**

- Single or Double air shower room
- Cargo showering room and goods shower channel
- Clean transfer window

- Strong cold dry line
- High temperature drying line
- Air shower spray disinfection room